

CHEYENNE FIBERGLASS COLUMNS

SIZING AND CAPACITIES

Bottom Diameter	Lengths (Feet)											Load Bearing Capacity
	8'	9'	10'	12'	14'	16'	18'	20'	22'	24'	26'	
8"	X	X	X									8,000 lbs
10"	X	X	X	X								10,000 lbs
12"	X	X	X	X	X	X	X					18,000 lbs
14"	X	X	X	X	X	X	X					20,000 lbs
16"				X	X	X	X	X				22,000 lbs
18"				X	X	X	X	X				24,000 lbs
20"				X	X	X	X	X	X	X		26,000 lbs
22"				X	X	X	X	X	X	X		28,000 lbs
24"				X	X	X	X	X	X	X	X	30,000 lbs
28"								X	X	X		35,000 lbs
30"								X	X	X		35,000 lbs
36"								X	X	X		35,000 lbs
Bottom Diameter may be nominal depending on the length of column												
Custom sizes available – please contact us												

Bottom Diameter	Top Diameter	Top Diameter w/Build-Up	Interior Clearance	Wall Thickness	Load Bearing Capacity
8"	6 1/4"	6 3/4"	6"	0.125"	8,000 lbs
10"	8"	8 1/2"	7 3/4"	0.125"	10,000 lbs
12"	10"	10 1/2"	9 3/4"	0.125"	18,000 lbs
14"	12"	12 1/2"	11 3/4"	0.125"	20,000 lbs
16"	13 1/2"	14"	13 1/4"	0.125"	22,000 lbs
18"	15"	15 5/8"	14 3/4"	0.125"	24,000 lbs
20"	17"	17 3/4"	16 5/8"	0.125"	26,000 lbs
22"	18 1/2"	19 1/4"	18 1/8"	0.125"	28,000 lbs
24"	20"	20 3/4"	19 9/16"	0.125"	30,000 lbs
28"	23 1/2"	25 1/2"	22 9/16"	0.125"	35,000 lbs
30"	25"	27"	24 9/16"	0.125"	35,000 lbs
36"	30"	32"	29 9/16"	0.125"	35,000 lbs
Bottom Diameter may be nominal depending on the length of column					
Custom sizes available – please contact us					

68 East Dudley Town Rd
Bloomfield, CT 06002

Tel: 1.800.676.8840
Fax: 1.866.676.3188
www.cheyennecompany.com

